



Name: S44-110A/120A/130A Flame/Graphite Furnace Atomic Absorption Spectrophotometer

**Description:**

**FEATURES:**

1 Innovated rich oxygen air-acetylene flame analysis technique(WFX-110A):

The patented flame analysis technique adopting rich oxygen air-acetylene flame as the substitution for nitrous oxide-acetylene flame for high temperature element analyses, such as Ca, Al, Ba, W, Mo, Ti, V, etc. Flame temperature is continuously adjustable between 2300-2950°C, with makes it possible to choose the best atomization temperature for different elements. It features easy operation, low analysis cost and wide flame AAS analytical range. Rich oxygen flame will not pollute the environment and is not harmful to human bodies. It's break-through in flame AAS analysis

2 Integrated flame/graphite furnace atomization system, changeable with flame emission burner

2.1 Automatically controlled changeover of the integrated flame and graphite furnace atomizer featuring easy operation time saving eliminates human labor.

2.2 A flame emission burner head can be installed to perform flame emission analysis to Alkali metals as K, Na etc.(WFX-110A/120A)

3 Accurate fully automated control system

3.1 Automatic multi-lamp turret, automatic adjustment of lamp current and optimization of light beam position

3.2 Automatic wavelength scanning and peak picking

3.3 Automatic spectral bandwidth changing

3.4 Automatic changeover between flame and graphite furnace operation, automatic optimization of position parameter automatic ignition

4 Reliable fully automatic graphite furnace analysis

4.1 Adopting FUZZY-PID and dual curve mode light-controlled temperature control technique, temperature auto-correction technique, ensures fast heating, good temperature reproducibility and high analytical sensitivity. The temperature control accuracy is less than 1%

4.2 Graphite furnace with pneumatic control and pressure lock ensures constant pressure and reliable contact

5 Perfect safety protection measures

5.1 Alarm and automatic protection to fuel gas leakage, abnormal flow, insufficient air pressure and abnormal flame extinction in flame system

5.2 Alarm and protection function to insufficient carrier gas and protective gas pressure, insufficient cooling water supply over-heating in graphite furnace system

6 Advance and reliable electronic design

6.1 Adopting large-scale programmable logic array and Inter I2C bus technology

6.2 European type sockets and AMP adapters with high reliability to ensure long term reliability of the whole electronic system

7 Easy and practical analysis software

7.1 Easy-to-use AAS analysis software is made under Windows operating system, realizing fast parameter setting and optimization

7.2 Automatic display of measured data, automatic calculation and analytical result automatic print out.

SPECIFICATIONS:

Main Specification	Wavelength range	190-900nm
	Wavelength accuracy	Better than $\pm 0.25\text{nm}$
	Resolution	Two spectral lines of Mn at 279.5nm and 279.8nm can be separated with spectral bandwidth of 0.2nm and valley-peak energy ratio less than 30
	Baseline stability	0.004A/30min
	Background correction	The D2 lamp background correction capability at 1A is better than 30 times The S-H background correction capability at 1.8A is better than 30 times only for WFX-110A/120A
Hollow Cathode Lamps	Lamp turret	6-lamp turret (WFX-110A/120A), 4-lamp turret (WFX-130A); Auto-alignment, fully automated scan and peak-picking.
	Lamp current adjustment	400Hz square wave pulse Wide pulse current: 0~25mA, Narrow pulse current: 0~10mA
	Lamp power supply mode	400Hz square wave pulse; 100Hz narrow square wave pulse+400Hz wide square wave pulse (WFX-110A/120A)
Optical System	Monochromator	Single beam, Czerny-Turner design grating monochromator
	Grating	1800 l/mm
	Focal length	277mm
	Blazed Wavelength	250nm
	Spectral Bandwidth	0.1nm, 0.2nm, 0.4nm, 1.2nm, automatic change
Flame Atomizer	Burner	10cm single slot all-titanium burner
	Spray chamber	Corrosion resistant all-plastic spray chamber
	Nebulizer	High efficiency glass nebulizer with metal sleeve, sucking up rate: 6-7ml/min
Emission burner provided with WFX-110A/120A		
Graphite Furnace	Temperature range	Room temperature~3000°C
	Heating rate	2000°C/s
	Graphite tube dimensions	28mm(L)×8mm(OD)
	Characteristic mass	Cd 0.5 ×10 <sup>-12</sup> g, Cu 5 ×10 <sup>-12</sup> g, Mo 1×10 <sup>-11</sup> g
	Precision	Cd 3%, Cu 3%, Mo 4%
Detection and Data Processing System	Detector	R928 Photomultiplier with high sensitivity and wide spectral range.
	Software	Windows operating system
	Analytical method	Working curve auto-fitting; standard addition method; automatic sensitivity correction, automatic calculation of concentration and content.
	Repeat times	Maximum 20 times of repeat measurement, automatic calculation of mean value, standard deviation and relative standard deviation.

	Multi-task Functions	Sequential measurement for multi-element determination in one sample
	Condition reading	With model function
	Result printing	Measurement data and final analytical report printout, editing with Ex
	Standard RS-232 serial port communication	
Characteristic Concentration and Detection Limit	Normal Air-C <sub>2</sub> H <sub>2</sub> flame Oxygen-rich Air-C <sub>2</sub> H <sub>2</sub> flame	Cu: Characteristic concentration 0.025mg/L, Detection limit 0.006mg/L;
		Ba: Characteristic concentration 0.22mg/L
		Al: Characteristic concentration 0.4mg/L
Function Expansion	Hydride vapor generator can be connected for hydride analysis	
Dimensions and weight	Main unit	102×49×54cm, unpacked 80kg
	Graphite furnace	42×42×46cm, unpacked 50kg



Oxford House, 20 Oxford St Newbury, Berkshire. RG14 1JB UK. Offices in UK, EU, Dubai  
[sales@spectrolab.eu](mailto:sales@spectrolab.eu) [sales@spectrolab.co.uk](mailto:sales@spectrolab.co.uk)